



Specifications Ledvance LED  
Floodlight Flex White 130W 19100lm  
55x120D - 830 Warm White | IP66 -  
Asymmetrical

[View Product](#)

General Information

|                          |                                                             |
|--------------------------|-------------------------------------------------------------|
| SKU                      | 252339                                                      |
| EAN                      | 4099854373329                                               |
| Brand                    | Ledvance                                                    |
| Manufacturer Name        | FLOODLIGHT FLEX ASYMMETRIC 55 X 120 130W ML 830 A55X120 WAL |
| Any Lamp all-in warranty | 5 Years                                                     |
| Average Lifetime (h)     | 120000                                                      |

Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Technology                  | LED Integrated  |
| Wattage                     | 130             |
| Replaces (Watt)             | 150             |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Not Dimmable    |
| Colour Code                 | 830 Warm White  |
| Colour temperature (Kelvin) | 3000 Warm White |
| Colour Rendering (Ra)       | 80-89           |
| Colour of Light             | White           |
| Light colour options        | Single Color    |
| Luminous Flux (Lumen)       | 19100           |
| Luminous Efficacy (lm/W)    | 147             |

|                       |                |
|-----------------------|----------------|
| Beam Angle (degree)   | 55x120         |
| Power factor          | >0.90          |
| Product Type Category | LED Floodlight |

## Fixture Information

|                        |                    |
|------------------------|--------------------|
| Mounting Method        | Surface            |
| Fixture Connection     | Screwless terminal |
| Light Distribution     | Asymmetrical       |
| IP-rating              | IP66               |
| Impact Protection (IK) | IK08 - 5 joules    |
| Operating Temperature  | -30 to +50         |
| Colour of the Fixture  | White              |
| Housing                | Aluminium          |
| Colour of material     | White              |
| Emergency Lighting     | No Emergency Unit  |

## Dimensions

|             |     |
|-------------|-----|
| Length (mm) | 492 |
| Width (mm)  | 361 |
| Height (mm) | 68  |

## Sensor Information

Type of sensor

**Why Any-lamp?**  
No Sensor



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process