



Specifications Ledvance LED Streetlight Urban Villa Retrofit 40W 4800lm 50x150d - 722 Extra Warm White | IP66 - Dali Dimmable - Asymmetrical

[View Product](#)

General Information

|                          |                                                 |
|--------------------------|-------------------------------------------------|
| SKU                      | 256412                                          |
| EAN                      | 4099854609381                                   |
| Brand                    | Ledvance                                        |
| Manufacturer Name        | URBAN VILLA RETROFIT ASYMMETRIC 40W 722 A50X150 |
| Any Lamp all-in warranty | 5 Years                                         |
| Average Lifetime (h)     | 100000                                          |

Technical Information

|                             |                       |
|-----------------------------|-----------------------|
| Technology                  | LED Integrated        |
| Wattage                     | 40                    |
| Replaces (Watt)             | 120                   |
| Voltage (V)                 | 220-240               |
| Dimmable                    | Dimmable with Dali    |
| Colour Code                 | 720 Extra Warm White  |
| Colour temperature (Kelvin) | 2200 Extra Warm White |
| Colour Rendering (Ra)       | 70-79                 |
| Colour of Light             | White                 |
| Light colour options        | Single Color          |
| Luminous Flux (Lumen)       | 4800                  |
| Luminous Efficacy (lm/W)    | 120                   |

|                       |                 |
|-----------------------|-----------------|
| Beam Angle (degree)   | 50x150          |
| Power factor          | >0.90           |
| Product Type Category | LED Streetlight |

## Fixture Information

|                        |                   |
|------------------------|-------------------|
| Mounting Method        | Post top          |
| Optical Cover          | Glass             |
| Light Distribution     | Asymmetrical      |
| IP-rating              | IP66              |
| Impact Protection (IK) | IK08 - 5 joules   |
| Operating Temperature  | -20 to +45        |
| Colour of the Fixture  | Black             |
| Housing                | Steel             |
| Emergency Lighting     | No Emergency Unit |

## Dimensions

|             |     |
|-------------|-----|
| Length (mm) | 320 |
| Width (mm)  | 320 |
| Height (mm) | 134 |

## Sensor Information

|                |           |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|

**Why Any-lamp?**



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

